

Advanced Vehicle GPS Tracker



3G/4G network

Has two versions running on WCDMA(Iridium optional) and LTE Cat M1/Cat NB1 networks respectively.

Mobileye Fleet Safety

Compatible with Mobileye collision avoidance system to keep your drivers and assets safe.

Garmin Fleet Tracking

Streamline dispatching with Garmin integration to further improve business efficiencies.

Multifunctional

Support CAN bus, camera, LED display, fuel/temperature sensor, iButton.



APPLICATION



Truck



Garbage truck



Armor cash carrier



Ambulance

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	105 mm x 65 mm x 26 mm
Weight	190g
Power supply	T622G & T622E: DC 11–36 V/1.5 A T622G_F9: DC 11.4–36 V/1.5 A
Backup battery	400 mAh/3.7V
Operating temperature	T622G & T622E: -20°C to 55°C T622G_F9: -10°C to 55°C
Operating humidity	5% to 95%
Working hour	53 hours in power-saving mode 5.5 hours in normal mode
Sensor	3-axis accelerometer
Memory	8 MB buffer
Positioning accuracy	2.5m
Frequency band	T622G: UMTS/HSDPA: 800/850/900/1900/2100 MHz GSM/GPRS: 850/900/1800/1900 MHz
	T622G_F9: UMTS/HSDPA: 800/850/900/1900/2100 MHz GSM/GPRS: 850/900/1800/1900 MHz Iridium satellite: Frequency band: 1616–1626.5 MHz, Duplex mode: TDD, Multiplexing mode: TDMA/FDMA
	T622E: Cat M1 & NB1:LTE FDD: B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B26/B28 LTE TDD: B39(for Cat M1 only) EGPRS: 850/900/1800/1900



ACCESSORIES

T622 Series tracker
GPS antenna
3G/4G antenna
Iridium antenna(T622G_F9)
I/O cable
USB cable
CD download card



OPTIONAL ACCESSORIES

Camera
iButton
LLS sensor
LED display
A76 ultrasonic fuel level sensor
Garmin navigator
A53 fuel level sensor
A52 digital temperature sensor + A61 sensor box



+86(755)83462818



www.meitrack.com



info@meitrack.com



6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038