

3G Plug & Play Vehicle GPS Tracker



Plug & play

This tracker with OBD II connector is aimed to achieve fast and easy installation.

Disconnect alert

An alert will be generated when the device is removed from the OBD connector.

Regular maintenance

Ensure the safety, reliability, drivability, comfort and longevity of a car.

Multiple alerts & reports

Support speeding/SOS/geo-fence alert, ACC ON & OFF/mileage/cornering report etc.



APPLICATION



Private car



Taxi



Truck

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	69.8 mm x 51.8 mm x 31.8 mm
Weight	60g
Power supply	DC 12 V/24V 1A
Backup battery (optional)	170 mAh/3.7 V (24 hours in power-saving mode; 1.5 hours in normal mode)
Power consumption	Current in standby mode: 68 mA
Operating temperature	-20°C to 55°C
Operating humidity	5% to 95%
LED indicator	2 indicators showing WCDMA, GSM and GPS status
Button/Switch	1 SOS button 1 power button
Memory	8 MB buffer
Sensor	3-axis accelerometer
Frequency band	TC68SG: UMTS/HSDPA: 800/850/900/1900/2100 MHz GSM/GPRS: 850/900/1800/1900 MHz TC68SG_A: UMTS/HSDPA: 850/1900 MHz TC68SG_E: UMTS/HSDPA: 900/2100 MHz GSM/GPRS: 900/1800 MHz
GPS sensitivity	-161 dB
Positioning accuracy	2.5m
I/O port	1 USB port



ACCESSORIES

TC68SG Tracker
Backup battery (170 mAh/3.7 V)
CD download card



OPTIONAL ACCESSORIES

OBD extension cord
Velcro
USB cable



+86(755)83462818



www.meitrack.com



info@meitrack.com



6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038