

4G WiFi Plug & Play Vehicle GPS Tracker



Plug & play

This tracker with OBD connector can be fastly and easily installed.

4G WiFi hotspot

Act as an in-vehicle WiFi hotspot, up to 8 WiFi enabled devices.

SOS button

An instant alert will be received when the SOS button is pressed.

Disconnect alert

When the device is removed from the OBD connector, an alert will be generated.



APPLICATION



Private car



Taxi



Truck

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	67 mm x 51 mm x 23.5 mm
Weight	60g
Power supply	DC 11.5–36 V / 1 A
Backup battery	110 mAh/3.7 V
Battery life	Power-saving mode: 12 hours; Normal working mode: 1 hour
Power consumption	Current in standby mode: 100 mA
Operating temperature	-20 °C to 55 °C
Operating humidity	5% to 95%
LED indicator	2 LED indicators showing GSM and GPS status
Button/Switch	1 SOS button
Microphone	Internal microphone
Memory	8 MB buffer
Sensor	3-axis accelerometer
Frequency band	TC68SL-E: GSM:900/1800MHz WCDMA:B1/B5/B8 FDD:B1/B3/B5/B7/B8/B20 TDD:B38/B40/B41 TC68SL-A: WCDMA:B2/B4/B5 FDD:B2/B4/B12 TC68SL-J: WCDMA:B1/B6/B8/B19 FDD:B1/B3/B8/B18/B19/B26 TDD:B41 TC68SL-AU: GSM:850/900/1800/1900MHz WCDMA:B1/B2/B5/B8 FDD:B1/B2/B3/B4/B5/B7/B8/B28 TDD:B40
GPS sensitivity	-161 dB
Positioning accuracy	2.5m
I/O port	1 USB port
WiFi function (optional)	2.4 GHz WiFi hotspot




ACCESSORIES

TC68SL Tracker
USB cable
CD download card



OPTIONAL ACCESSORIES

OBD extension cord
Velcro



+86(755)83462818



www.meitrack.com



info@meitrack.com



6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038