

8CH 1080P HDD & SD Card Mobile DVR



DUAL SYSTEMS: MDVR+TRACKER

Remain the advantages of GPS tracking, and add DVR functions to meet more demands of applications.

HIGH STABILITY

Independent 4G communication. The tracker and peripherals can work properly no matter when the ACC is on or off.

ALL-IN-ONE PLATFORM

The MS03 platform that integrates video surveillance with GPS tracking.

VIDEO RECORDING

8-channel 1080P live video recording, support OSD overlay for video recording.



VIDEO MANAGEMENT

Support video searching, playback and downloading via the platform.



MD811H

Working Principles: Meitrack VS Other Manufacturers



SPECIFICATIONS

ITEM	PARAMETER	SPECIFICATIONS
Audio and video	Video input	8-channel 1080P@25FPS live video recording
	Video output	1-channel CVBS + 1-channel VGA
	Compression standard	H.264/H.265 (optional)
	Image display	Support one-image and nine-image display
	Audio compression	G.726
	Audio input	9-channel audio input; 8-channel AV-IN interface; 1-channel voice intercom interface
	Audio output	1-channel independent audio DC blocking output (connected to the AV-OUT interface, VGA aviation connector, or handset interface)
	Video search and playback	Search and play back videos based on the channel, recording type, or time.
	Recording method	Simultaneously record the ACC, alert, sound, and video.
	Storage medium	1 SD card and 1 SATA hard drive/SSD hard drive
Communication and positioning	3G/4G	MD811H_GE4PG3W1 2G GSM: B3/B8, 3G WCDMA: B1/B8 4G FDD: B1/B3/B7/B8/B20/B28A MD811H_GA4PG3W1 3G WCDMA: B2/B4/B5, 4G FDD: B2/B4/B12 MD811H_GV4PG3W1 4G FDD: B4/B13 MD811H_GAU4PG3W1 2G GSM: B2/B3/B5/B8, 3G WCDMA: B1/B2/B5/B8 4G FDD: B1/B2/B3/B4/B5/B7/B8/B28, 4G TDD: B40 MD811H_GJ4PG3W1 3G WCDMA: B1/B6/B8/B19 4G FDD: B1/B3/B8/B18/B19/B26, 4G TDD: B41
	WiFi	802.11 b/g/n; frequency: 2.4 GHz
	GPS/GLONASS	Detect the insertion, pull-out, and short circuit of the antenna.
	Others	
Others	Dimension	177 mm x 162 mm x 63mm
	Weight	2000g (excluding the hard disk)
	Power input	DC: 8V–36V/A
	Power consumption	Start the host audio and video: about 8 W Connect 8 cameras: about 24 W in the daytime (connect a display: 29 W); about 32 W at night (connect a display: 37 W) Connect a single camera: 50–100 mA in the daytime; 200–250 mA at night
	Operating temperature	-20°C to 70°C



ACCESSORIES

MD811H MDVR
Power & ACC cable
I/O cable
USB cable
GPS antenna
3G/4G antenna
WiFi antenna
Hard disk lock key
Cameras splitter (1 to 2)
CD download card



OPTIONAL ACCESSORIES

Cameras(different types)
SD card
SSD/HDD (2.5 inches)
Display (AV-OUT)
Display (VGA)
Microphone & speaker
Ultrasonic fuel level sensor
RFID reader
RFID tag(key)
LED display
Camera extension cable
Handset
iButton
iButton key
Temperature sensor
A61 sensor Box
Fuel sensor



+86(755)83462818



www.meitrack.com



info@meitrack.com



5/F, International Internet Finance Pioneer Park, No. 1, Taohua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038