

Advanced Vehicle GPS Tracker



**T622
Series**

3G/4G network

Has two versions running on WCDMA(Iridium optional) and LTE Cat M1/Cat NB2 networks respectively.

Mobileye Fleet Safety

Compatible with Mobileye collision avoidance system to keep your drivers and assets safe.

Garmin Fleet Tracking

Streamline dispatching with Garmin integration to further improve business efficiencies.

Multifunctional

Support CAN bus, camera, LED display, fuel/temperature sensor, iButton.



APPLICATION



Truck



Garbage truck



Armor cash carrier



Ambulance

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	105 mm x 65 mm x 26 mm
Weight	190g
Power supply	DC 11.4–36 V/1.5 A
Backup battery	400 mAh/3.7V
Power consumption	Current in sleep mode: 11 mA
Operating temperature	-10°C to 55°C
Operating humidity	5% to 95%
Working hour	45 hours in power-saving mode 4 hours in normal mode
LED indicator	Green indicator showing the GSM signal Blue indicator showing the GPS signal
Button/Switch	1 power button
Sensor	3-axis accelerometer (used to wake the device up by vibration and detect towing alerts)
Memory	8 MB buffer
GNSS	GPS
GPS sensitivity	-161 dB
Positioning accuracy	2.5m
Frequency band	T622G: UMTS/HSDPA: 800/850/900/1900/2100 MHz GSM/GPRS: 850/900/1800/1900 MHz
	T622G_F9: UMTS/HSDPA: 800/850/900/1900/2100 MHz GSM/GPRS: 850/900/1800/1900 MHz Iridium satellite: Frequency band: 1616–1626.5 MHz, Duplex mode: TDD, Multiplexing mode: TDMA/FDMA
	T622E: Cat M: B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B26/B27/B28/B66/B85 Cat NB: B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B28/B66//B71/B85 GSM: 850/900/1800/1900MHz



ACCESSORIES

T622 Series tracker
External GPS antenna
External 3G/4G antenna
External Iridium antenna(T622G_F9)
I/O cable(1 meter, without SOS button)
Micro serial USB cable
CD download card



OPTIONAL ACCESSORIES

SOS button
Relay (12 V/24 V)
RFID reader
Garmin navigator
Camera
iButton (T622G & T622E)
A53 fuel level sensor (T622G & T622E)
A52 digital temperature sensor + A61 sensor box (T622G & T622E)
A76 ultrasonic fuel level sensor
Liquid level sensor (LLS) sensor



+86(755)83462818



www.meitrack.com



info@meitrack.com



5/F, International Internet Finance Pioneer Park, No. 1, Taohua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038