

ACP602 (ADAS) Camera Specifications



Applicable Model: MD500S

Change History

| | | | |
|------------|-------------------------------------|---------------|------------------------|
| File Name | ACP602 (ADAS) Camera Specifications | | |
| Project | MD500S | Creation Date | 2024/3/5 |
| Subproject | Accessory Specifications | Total Pages | 5 |
| Version | V1.0 | Confidential | External Documentation |

Contents

1 Copyright and Disclaimer - 4 -




2 Product Specifications - 4 -

3 Enclosure structure diagram..... - 4 -

4 Standard Configuration..... - 5 -

1 Copyright and Disclaimer

Copyright © Meitrack Group 2024. All rights reserved.

 ,  and  are trademarks that belong to Meitrack Group and its subsidiary.

The user manual may be changed without notice.


Without prior written consent of Meitrack Group, this user manual, or any part thereof, may not be reproduced for any purpose whatsoever, or transmitted in any form, either electronically or mechanically, including photocopying and recording.

Meitrack Group shall not be liable for direct, indirect, special, incidental, or consequential damages (including but not limited to economic losses, personal injuries, and loss of assets and property) caused by the use, inability, or illegality to use the product or documentation.

2 Product Specifications

| Item | Specifications |
|-----------------------|--|
| Exterior shape | Plastic shell |
| Exterior color | Black |
| Imaging device | 2 million pixel CMOS |
| Infrared | Without infrared |
| Effective Pixels | 1280(H)*720(V) |
| Minimum illumination | 0.01LUX/F1.2 |
| Horizontal Resolution | AHD 720P 1 million pixels |
| Scanning frequency | 25Hz |
| Signal system | PAL |
| Audio | Without audio |
| Video output | 1.0V |
| White balance | Automatic |
| Shutter | 1/50~1/100000s |
| Signal-to-noise ratio | >46dB |
| Current | <200mA |
| Voltage | DC 3.3V~5V±10% |
| Waterproof rating | IP65 |
| Working environment | Temperature -20°C~+70°C; Humidity -0°C~+90°C |
| Camera angle | Lens: 6mm Horizontal: 50° |
| Operating environment | Inside the car |
| Pigtail length | 500CM ± 10 |
| Connector | Customer supplied wire |

3 Enclosure structure diagram



4 Standard Configuration

| Order | Name | Quantity | Unit | Remarks |
|-------|--------------------------------------|----------|------|----------|
| 1 | In-car camera | 1 | Pcs | Standard |
| 2 | Install screw kit | 2 | Pcs | Standard |
| 3 | Double-sided shock-absorbing sticker | 1 | Pcs | Standard |



If you have any questions, do not hesitate to email us at info@meitrack.com.